

2U Equipment Holder



Cantilever Tray



3U Sub-Rack



Drawer



Wall Mount Brackets

2U Equipment Holder

Equipment Holders are useful for light-weight equipments that are not compliant to 19" standard. These 2U front mounting holders, commonly used in wall mount enclosures and open frame systems, are equipped with the strength to hold and store equipments of up to 30kg.

Ordering Information and Physical Characteristics:

Model No.	Width(mm)	Depth(mm)	Type	Colour	Remarks
So632	440	300	Vented	Light Grey	2U Front Mount
So632BL	440	300	Vented	Black	2U Front Mount
So631	440	400	Vented	Light Grey	2U Front Mount
So631BL	440	400	Vented	Black	2U Front Mount

*Finish with Epoxy Powder Coating: RAL7035 Light Grey or RAL9004 Black

Cantilever Tray

Cantilever Trays are uniquely proposed solutions to hold non 19" equipments on a Open Frame System. It's appropriate design allows for the weight of the equipments to be evenly distributed across the depth of the tray with the mounting position situated at the centre.

Ordering Information and Physical Characteristics:

Model No.	Width(mm)	Depth(mm)	Type	Colour	Remarks
So633	440	600	Vented	Light Grey	2U Mount c/w 4 x Front and Rear Adjustable Brackets
So633BL	440	600	Vented	Black	
So634	440	700	Vented	Light Grey	
So634BL	440	700	Vented	Black	

*Finish with Epoxy Powder Coating: RAL7035 Light Grey or RAL9004 Black

3U Sub-Rack

As its name implies, 3U sub-rack is a alternate housing for equipments in a 19" cabinet. Essentially equipped with a internal din rail and a cut-out, 3U sub-rack supplies an ideal solution for the storage of various circuit breakers.

Wall Mount Brackets

Wall Mount Brackets are used for housing 19" equipments in space constrained deployments. The "Open-Concept" frame work offers high flexibility and allow for the easy accessibility to equipments.

Drawer

Drawers provide another mean of securing equipments which require additional handling in a 19" cabinet. Their security feature in the lock and availability in various sizes allow for the safe storage of equipments having different requirements.

Ordering Information and Physical Characteristics:

Model No.	RU	Height Dimension	Depth Dimension
3U-Sub	3U	132mm	68mm
4U-Sub	4U	178mm	68mm

*Finish with Epoxy Powder Coating: RAL7035 Light Grey or RAL9004 Black
*19" Front Rack Mount c/w Earthing Stud and 1 x Omega Din rail pre-installed

Ordering Information and Physical Characteristics:

Model No.	RU	Height Dimension	Depth Dimension
SWMB-4	4U	180mm	304.8mm
SWMB-6	6U	269mm	304.6mm

*Finish with Epoxy Powder Coating: RAL9004 Black

Ordering Information and Physical Characteristics:

Model No.	RU	Height Dimension	Depth Dimension
So602	2U	88mm	360mm
So603	3U	132mm	360mm
So604	4U	178mm	360mm
So605	5U	222mm	360mm

*Finish with Epoxy Powder Coating: RAL7035 Light Grey or RAL9004 Black
*19" Front Rack Mount c/w Sliding bars and Camlock Set